



Easily accessible control levers in the right console



Agrofarm 115 G/GS platform available

AGROFARM
115 G/GS
DEPENDABLE POWER.

AGROFARM 115 G/GS

The ideal answer to a wide variety of needs.

The Agrofarm 115 G/GS provides the ideal answer to a wide variety of needs: offering productivity and versatility in the field, superior manoeuvrability for general farm tasks and speed for quick road transport. These tractors combine compact dimensions with high technology equipment to ensure outstanding results in all working conditions. A unique feature, their single pump high pressure injection system uses a single pump for each cylinder delivering superlative performance with extraordinary reliability.

●: standard O: optional -: not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time.

MACHINE SPECIFICATIONS		AGROFARM 115 G/GS
ENGINE		
Manufacturer		SDF
Model		1000.4 WTI
Emission		Stage II
Cylinders/Displacement	n°/cc	4/4000
Intake		Turbo intercooler
Max. power (2000/25/CE)	kW/HP	81/110
Maximum torque	Nm	396
Air filter with dust ejector		●
Exhaust silencer on cab A-pillar		●
Fuel tank capacity	litres	150
TRANSMISSION		
Number of speeds (Mechanical)		20+20
Minimum speed with supercreeper gear	km/h	0.45
Minimum speed	km/h	40
Powershuttle		G - / GS ●
PTO		
Rear PTO	rpm	540/540ECO/1000/1000ECO
Ground Speed PTO		O
Front PTO (optional)	rpm	1000
AXLES AND BRAKES		
4WD front axle with brakes		●
Front wheel drive engagement		Mechanical
Front and rear differential lock engagement		Electrohydraulic
Hydrostatic steering with independent pump		●
HYDRAULIC SYSTEM AND LIFT		
Fixed displacement pump flow (standard/optional)	l/min	56
Auxiliary rear mechanical distributors	n°	1/2/3/4
Rear lift control (Mechanical)		●
Maximum rear lift capacity	kg	4800
Maximum front lift capacity (optional)	kg	2000
DRIVING POSITION		
Cab with A/C		O
Platform		O
Side mounted levers		●
DIMENSIONS AND WEIGHTS		
Width (min.-max.)	mm	2320-2340
Wheelbase (4WD)	mm	2340
Total unladen weight (min.-max.)	kg	4107-4660
Maximum permissible total weight	kg	7200